

Đ~Đ^{1/2}Ñ,ĐμÑ€Đ^{1/2}ĐμÑ,-Đ^{1/4}Đ°Đ³Đ°Đ·Đ,Đ^{1/2}

ĐœĐ°Đ³Đ°Đ·Đ,Đ^{1/2}

Đ‘Đ»Đ^{3/4}Đ° Đ°Đ^{3/4}Đ^{1/4}Đ^{1/4}ÑfÑ,Đ°Ñ†Đ,Đ,
ĐŸĐ^{3/4}Đ»Đ,Ñ•ĐμÑ€Đ²Đ,Ñ•
ĐŁÑ•Ñ,Ñ€Đ^{3/4}Đ¹Ñ•Ñ,Đ²Đ^{3/4}
Đ°Đ^{3/4}Đ^{1/4}Đ^{1/4}ÑfÑ,Đ°Ñ†Đ,Đ,
Đ³Ñ€Đ^{3/4}Đ·Đ^{3/4}Đ·Đ°Ñ%Đ,Ñ%ĐμĐ^{1/2}Đ^{1/2}Đ^{3/4}Đμ

1 180.00 Đ ÑfĐ±.



3 Ñ‘Đ»ĐμĐ¹Ñ,Đ° + 1 Đ»Đ,Đ^{1/2}Đ,Ñ• RS-485 + Đ¿Đ,Ñ,Đ°Đ^{1/2}Đ,Đμ, -40….+50°
[Đ~Đ^{1/2}Ñ,Đ^{3/4}Ñ€Đ^{1/4}Đ°Ñ†Đ,Ñ• Đ^{3/4}Đ¿Ñ€Đ^{3/4}Đ·Đ°Đ²Ñ†Đμ](#)