

Đ~Đ<sup>1/2</sup>Ñ,ĐμÑ€Đ<sup>1/2</sup>ĐμÑ,-Đ<sup>1/4</sup>Đ°Đ<sup>3</sup>Đ°Đ·Đ,Đ<sup>1/2</sup>

ĐœĐ°Đ<sup>3</sup>Đ°Đ·Đ,Đ<sup>1/2</sup>

**MicroDigital MDR-16700 16-Ñ,Đ,  
Đ°Đ°Đ<sup>1/2</sup>Đ°Đ»ÑœĐ<sup>1/2</sup>Ñ<Đ<sup>1</sup>  
Đ<sup>2</sup>Đ,Đ´ĐμĐ<sup>3/4</sup>Ñ€ĐμĐ<sup>3</sup>Đ,Ñ•Ñ,Ñ€Đ°Ñ,Đ<sup>3/4</sup>Ñ€Ñ•  
Đ,Đ<sup>1/2</sup>Ñ,ĐμÑ€Đ<sup>1/2</sup>**

36 800.00 Đ ÑfĐ±.



MicroDigital MDR-16700 16-Ñ,Đ, Đ°Đ°Đ<sup>1/2</sup>Đ°Đ»ÑœĐ<sup>1/2</sup>Ñ<Đ<sup>1</sup> Đ<sup>2</sup>Đ,Đ´ĐμĐ<sup>3/4</sup>Ñ€ĐμĐ<sup>3</sup>Đ,Ñ•Ñ,Ñ€Đ°Ñ,Đ<sup>3/4</sup>Ñ€Ñ•  
Đ,Đ<sup>1/2</sup>Ñ,ĐμÑ€Đ<sup>1/2</sup>ĐμÑ,Đ<sup>3/4</sup>Đ<sup>1/4</sup> 16 Đ°Đ°Đ<sup>1/2</sup>. Đ<sup>2</sup>Đ,Đ´ĐμĐ<sup>3/4</sup>, 1 Đ°Đ°Đ<sup>1/2</sup>. Đ°ÑfĐ´Đ,Đ<sup>3/4</sup>, MPEG-4,  
ĐŸĐμĐ<sup>1/2</sup>Ñ,Đ°Đ¿Đ»ĐμĐ°Ñ•, 10/100 Mbit Ethernet, ĐŸĐž Ñ†ĐμĐ<sup>1/2</sup>Ñ,Ñ€. Đ¿Đ<sup>3/4</sup>Ñ•Ñ,Đ° Đ<sup>1/2</sup>Đ°Đ±Đ». (CMS),  
RS-485, RS-232, Đ·Đ°Đ¿Đ,Ñ•Ñœ - 400 Đ°/Ñ•ĐμĐ° (352Ñ...288), 200 Đ°/Ñ•ĐμĐ° (704Ñ...288), 100...  
[Đ~Đ<sup>1/2</sup>Ñ,Đ<sup>3/4</sup>Ñ€Đ<sup>1/4</sup>Đ°Ñ†Đ,Ñ•Đ<sup>3/4</sup>Đ¿Ñ€Đ<sup>3/4</sup>Đ´Đ°Đ<sup>2</sup>Ñ†Đμ](#)