

Đ~Đ^{1/2}Ñ,ĐμÑ€Đ^{1/2}ĐμÑ,-Đ^{1/4}Đ°Đ³Đ°Đ·Đ,Đ^{1/2}

ĐœĐ°Đ³Đ°Đ·Đ,Đ^{1/2}

**MicroDigital MDR-16700 16-Ñ,Đ,
Đ°Đ°Đ^{1/2}Đ°Đ»ÑœĐ^{1/2}Ñ<Đ¹
Đ²Đ,Đ´ĐμĐ^{3/4}Ñ€ĐμĐ³Đ,Ñ•Ñ,Ñ€Đ°Ñ,Đ^{3/4}Ñ€Ñ•
Đ,Đ^{1/2}Ñ,ĐμÑ€Đ^{1/2}**

36 800.00 Đ ÑfĐ±.



MicroDigital MDR-16700 16-Ñ,Đ, Đ°Đ°Đ^{1/2}Đ°Đ»ÑœĐ^{1/2}Ñ<Đ¹ Đ²Đ,Đ´ĐμĐ^{3/4}Ñ€ĐμĐ³Đ,Ñ•Ñ,Ñ€Đ°Ñ,Đ^{3/4}Ñ€Ñ•
Đ,Đ^{1/2}Ñ,ĐμÑ€Đ^{1/2}ĐμÑ,Đ^{3/4}Đ^{1/4} 16 Đ°Đ°Đ^{1/2}. Đ²Đ,Đ´ĐμĐ^{3/4}, 1 Đ°Đ°Đ^{1/2}. Đ°ÑfĐ´Đ,Đ^{3/4}, MPEG-4,
ĐŸĐμĐ^{1/2}Ñ,Đ°Đ¿Đ»ĐμĐ°Ñ•, 10/100 Mbit Ethernet, ĐŸĐž Ñ†ĐμĐ^{1/2}Ñ,Ñ€. Đ¿Đ^{3/4}Ñ•Ñ,Đ° Đ^{1/2}Đ°Đ±Đ». (CMS),
RS-485, RS-232, Đ·Đ°Đ¿Đ,Ñ•Ñœ - 400 Đ°/Ñ•ĐμĐ° (352Ñ...288), 200 Đ°/Ñ•ĐμĐ° (704Ñ...288), 100...
[Đ~Đ^{1/2}Ñ,Đ^{3/4}Ñ€Đ^{1/4}Đ°Ñ†Đ,Ñ•Đ^{3/4}Đ¿Ñ€Đ^{3/4}Đ´Đ°Đ²Ñ†Đμ](#)