

Đ~Đ^{1/2}Ñ,ĐμÑ€Đ^{1/2}ĐμÑ,-Đ^{1/4}Đ°Đ³Đ°Đ-Đ,Đ^{1/2}

ĐœĐ°Đ³Đ°Đ-Đ,Đ^{1/2}

Ai-D163 16-Ñ,Đ, Đ°Đ°Đ^{1/2}Đ°Đ»ÑœĐ^{1/2}Ñ<Đ¹
Ñ†Đ,Ñ,,Ñ€Đ^{3/4}Đ²Đ^{3/4}Đ¹

Đ²Đ,Đ´ĐμĐ^{3/4}Ñ€ĐμĐ³Đ,Ñ•Ñ,Ñ€Đ°Ñ,Đ^{3/4}Ñ€

33 396.00 Đ ÑfĐ±.



16-Ñ,Đ, Đ°Đ°Đ^{1/2}Đ°Đ»ÑœĐ^{1/2}Ñ<Đ¹ Ñ€ĐμĐ³Đ,Ñ•Ñ,Ñ€Đ°Ñ,Đ^{3/4}Ñ€, PAL 704x576,
ĐœĐμÑ...Đ^{1/2}Đ^{3/4}Đ»Đ^{3/4}Đ³Đ,Ñ•Ñ•Đ¶Đ°Ñ,Đ,Ñ•: H.264 DSP, Đ;Ñ,ĐμĐ;ĐμĐ^{1/2}Ñœ Ñ•Đ¶Đ°Ñ,Đ,Ñ•:
40:1-2400:1, Đ;Đ°Đ^{3/4}Ñ€Đ^{3/4}Ñ•Ñ,Ñœ Đ-Đ°Đ;Đ,Ñ•Đ,: 200 Đ^{1/4}Đ°Đ°Ñ•~167 Đ^{1/4}Đ,Đ^{1/2}. Đ°Ñ•,
Đ;Đ°Đ^{3/4}Ñ€Đ^{3/4}Ñ•Ñ,Ñœ Đ^{1/4}Đ^{3/4}Đ^{1/2}Đ,Ñ,Đ^{3/4}Ñ€Đ,Đ^{1/2}Đ³Đ° (PAL) 400 Đ°Đ°Đ´Ñ€Đ^{3/4}Đ²Đ²Ñ•ĐμĐ°ÑfĐ^{1/2}Đ´Ñf
Đ^{1/2}Đ° 16 Đ°Đ°Đ^{1/2}Đ°Đ»Đ^{3/4}Đ², Đ´Đ,Đ´ĐμĐ^{3/4}Đ²Ñ...Đ^{3/4}Đ´/Đ•ÑfĐ´Đ,Đ^{3/4}Đ²Ñ...Đ^{3/4}Đ´: BNCx16 / RCAx8,
Đ´Đ,Đ´ĐμĐ^{3/4}Đ²Ñ<Ñ...Đ^{3/4}Đ´/Đ•ÑfĐ´Đ,Đ^{3/4}Đ²Ñ<Ñ...Đ^{3/4}Đ´: BNCx1 / RCAx1, ĐYĐ^{3/4}Đ´Đ´ĐμÑ€Đ¶Đ°Đ°
Đ´Đ²ÑfÑ... Đ¶ĐμÑ•Ñ,Đ°Đ,Ñ... Đ´Đ,Ñ•Đ°Đ^{3/4}Đ² IDE, Đ ĐμĐ-ĐμÑ€Đ²Đ^{1/2}Đ^{3/4}Đμ
Đ°Đ^{3/4}Đ;Đ,Ñ€Đ^{3/4}Đ²Đ°Đ^{1/2}Đ,Đμ Đ^{1/2}Đ° USB Đ´Đ,Ñ•Đ°, ĐœÑ€ĐμĐ²Đ^{3/4}Đ¶Đ^{1/2}Ñ<Đμ Đ²Ñ...Đ^{3/4}Đ´Ñ< /
Đ²Ñ<Ñ...Đ^{3/4}Đ´Ñ<, VGA Đ²Ñ<Ñ...Đ^{3/4}Đ´, Đ;ĐμÑ,Ñœ RJ45 (100/10Mbps Ethernet), ĐYĐ,Ñ,Đ°Đ^{1/2}Đ,Đμ:
110-240VAC

[Đ~Đ^{1/2}Ñ,Đ^{3/4}Ñ€Đ^{1/4}Đ°Ñ†Đ,Ñ•Đ^{3/4}Đ;Ñ€Đ^{3/4}Đ´Đ°Đ²Ñ†Đμ](#)