

Đ~Đ^{1/2}Ñ,ĐμÑ€Đ^{1/2}ĐμÑ,-Đ^{1/4}Đ°Đ³Đ°Đ·Đ,Đ^{1/2}

ĐœĐ°Đ³Đ°Đ·Đ,Đ^{1/2}

ĐçÑ€Đ°Đ» 32-120

Đ^{1/4}Đ°Đ»Đ^{3/4}Đ³Đ°Đ±Đ°Ñ€Đ,Ñ,Đ^{1/2}Ñ(Đ¹

Đ²Đ,Đ´ĐμĐ^{3/4}Ñ€ĐμĐ³Đ,Ñ•Ñ,Ñ€Đ°Ñ,Đ^{3/4}Ñ€

22 500.00 Đ ÑfĐ±.



Đ^{1/4}Đ°Đ»Đ^{3/4}Đ³Đ°Đ±Đ°Ñ€Đ,Ñ,Đ^{1/2}Ñ(Đ¹ Đ²Đ,Đ´ĐμĐ^{3/4}Ñ€ĐμĐ³Đ,Ñ•Ñ,Ñ€Đ°Ñ,Đ^{3/4}Ñ€ 4 Đ²Đ,Đ´ĐμĐ^{3/4}, 2 Đ°ÑfĐ´Đ,Đ^{3/4},704×.576, SATA, Đ²Ñ•Ñ,Ñ€Đ^{3/4}ĐμĐ^{1/2}Đ^{1/2}Ñ(Đ¹, RS232, female DE-9, Fast Ethernet 10/100 Base-T, USB-A, 170×.100×.30 Đ^{1/4}Đ^{1/4}

[Vendor Information](#)